

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PATENT ABSTRACTS OF JAPAN

English Translation

65

(11)Publication number : 55-163868
(43)Date of publication of application : 20.12.1980

(51)Int.Cl.

H01L 23/48

(21)Application number : 54-071117
(22)Date of filing : 08.06.1979


(71)Applicant : FUJITSU LTD
(72)Inventor : AOKI TSUYOSHI
KUBOTA AKIHIRO
YAMAUCHI OSAMU
SUGIURA RIKIO

(54) LEAD FRAME AND SEMICONDUCTOR DEVICE USING THE SAME

(57)Abstract:

PURPOSE: To enhance the strength of an external connector in a lead frame of a resin molded semiconductor device and increase the density of a chip connector by forming thin chip carrying base of the lead frame and thin lead terminal formed therearound and thick external connecting lead terminal.

CONSTITUTION: A guide hole 5 is perforated at a metallic plate, and thin and thick portions A and B are formed by pressing. Then, a chip carrying base 2 and a lead terminal 3 are formed on the lead frame 1 by stamping. The semiconductor chip is carried on a chip carrying base 2, wire bonded to the lead terminal 3, and clamped from both front and rear surfaces of the molding frame, resin is filled to seal the semiconductor device.



LEGAL STATUS

[Date of request for examination]
[Date of sending the examiner's decision of rejection]
[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]
[Date of final disposal for application]
[Patent number]
[Date of registration]
[Number of appeal against examiner's decision of rejection]
[Date of requesting appeal against examiner's decision of rejection]
[Date of extinction of right]

Copyright (C); 1998,2000 Japan Patent Office

LEAD FRAME AND SEMICONDUCTOR DEVICE USING THE SAME

Patent Number: JP55163868
Publication date: 1980-12-20
Inventor(s): AOKI TSUYOSHI; others: 03
Applicant(s): FUJITSU LTD
Requested Patent: ☐ JP55163868
Application Number: JP19790071117 19790608
Priority Number(s):
IPC Classification: H01L23/48
EC Classification:
Equivalents:

Abstract

PURPOSE: To enhance the strength of an external connector in a lead frame of a resin molded semiconductor device and increase the density of a chip connector by forming thin chip carrying base of the lead frame and thin lead terminal formed therearound and thick external connecting lead terminal.
CONSTITUTION: A guide hole 5 is perforated at a metallic plate, and thin and thick portions A and B are formed by pressing. Then, a chip carrying base 2 and a lead terminal 3 are formed on the lead frame 1 by stamping. The semiconductor chip is carried on a chip carrying base 2, wire bonded to the lead terminal 3, and clamped from both front and rear surfaces of the molding frame, resin is filled to seal the semiconductor device.

Data supplied from the esp@cenet database - I2